

ACCURACY INTERNATIONAL AXMC

AXMC rifles are available in 338, .300 or .308 caliber. Armed with an AXMC caliber conversion kit, a user can easily change the original caliber in minutes.

CALIBERS

.338 Lap Mag | .300 Win Mag | .308 Win

WEIGHT

6.8kg (15lb)

with standard rail setup, empty magazine, no scope, 27" barrel, tactical muzzle brake

DIMENSIONS

Full length: 1250mm x 185mm x 100mm Stock folded: 1040mm x 185mm x 105mm with 27" barrel, tactical muzzle brake

FEATURES

Proofed steel action featuring Al's patent pending Quickloc quick release barrel system, bolted and bonded to aluminum chassis

30 MOA STANAG 4694 / Mil Std 1913 action and forend rail

6 lug, 60° bolt with AI combat proven leaf spring extractor

3 position safety

Two stage trigger adjustable for reach and trigger weight between 1.5 and 2kg

Detachable 10-round CIP length double stack magazine - can also be top loaded though the rifle ejection port

Left side magazine port cut out for ease of magazine insertion

BASE MODELS

Right side folding stock over bolt

Adjustable cheekpiece

Adjustable buttpad with spacers

Pistol grip

Flush cup sling attachment points

30 MOA STANAG 4694 / Mil Std 1913 action rail and 16" forend tube and rail

Double chamber standard muzzle brake

1 x 140mm plain accessory rail

2 x 80mm flush cup accessory rails

User manual

1 x 10 round double stack CIP magazine

COLORS

AX rifles benefit from a Cerakote ceramic

High performance

DARK EARTH

Tactical threaded double chamber muzzle brake for AI suppressor

ACCESSORIES

OPTIONS

STANAG 4694 / Mil std 1913 accessory rails to attach to Al's patented KeySlot™ mounting system

Al Bipod and mounts for other bipod brands (including Harris)

Rear butt spikes

Caliber conversion kits (also see reverse): .338 LM, .300 WM and .308 Win* comprising barrel, bolt & magazine *includes long action magazine converter

Handstop with sling loop and flush cup

Suppressor

Slings | Transit cases | Cleaning kits

polymer firearm coating. Choose from: Elite ultra high

in three unique Al colors

ELITE MIDNIGHT

performance for

unrivalled durability

ELITE SAND

AI BARREL OPTIONS

.338 LM: 20"/27" 1 in 9.35" twist, stainless steel, plain threaded for muzzle brake

.300 Win Mag: 20"/24"/26" 1 in 11" twist, stainless steel, plain threaded for muzzle brake

.308 Win: 20"/24"/26" 1 in 12" twist, stainless steel, plain threaded for muzzle brake

ALAXMC MULTICAL SYSTEM COMPONENTS



Changing caliber is as simple as ABC and takes just a few minutes...

A CHANGE BARREL

Loosen the barrel clamp screw with the pre-set torque wrench supplied and unscrew the barrel.

Hand tighten the selected caliber barrel and tighten the barrel clamp screw with the pre-set torque wrench.

B CHANGE BOLT

Slide the bolt from the rifle, take out the shroud / firing pin and insert it in the chosen caliber bolt. Slide the chosen bolt assembly into the rifle.

CHANGE MAGAZINE

Note: For 308/7.62mm caliber, insert the .308/7.62mm magazine converter into the magazine aperture before loading the magazine.



Accuracy International of North America Inc.

T: 540-368-3108

F: 540-368-3109

E: info@accuracyinternational.us

www.accuracyinternational.us

